

SD10PU200

High Current Density Surface Mount Schottky Rectifier

Description

This Schottky rectifier is designed for switch mode power supply and high frequency DC to DC converters.

Packaged in DFN 3.3mmx3.3mm, this device is intended for use in low voltage, high frequency, inverters, free-wheeling, by-pass diode and polarity protection applications. Its low profile was especially designed to be used in applications with space-saving constraints.

Features


- Very low conduction losses
- Negligible switching losses
- Extremely fast switching
- Low thermal resistance
- Avalanche capacity specified
- High junction temperature
- RoHS compliant package

Mechanical Data


- Case:DFN 3.3*3.3
- Molding compound meets UL 94 V-0 flammability

Packing & Order Information

3,000/Reel




RoHS
COMPLIANT



DIMENSIONS (mm are the original dimensions)

UNIT	A max.	A1	b	c	D	Dh	E	Eh	e	et	L1	L2	v	w	y	y1
mm	1	0.05	0.45	0.2	3.4	2.4	3.4	1.80	0.65	1.95	0.55	0.52	0.1	0.05	0.1	0.1
		0.00	0.25		3.2	2.2	3.2	1.58			0.45	0.35				

Graphic symbol



Device summary

Symbol	Value
IF(AV)	10A
VRRM	200V
Tj(max)	150°C
VF(typ)	0.78

SD10PU200

High Current Density Surface Mount Schottky Rectifier

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Maximum Ratings (Tc=25°C unless otherwise noted)

Parameter	Symbol	SD10PU200	Unit
Maximum repetitive peak reverse voltage	VRRM	200	V
Working peak reverse voltage	VRWM	140	V
Maximum DC blocking voltage	VDC	200	V
Maximum average forward rectified current	IF(AV)	10	A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	IFSM	160	A
Non-repetitive avalanche energy at 25 °C IAS = 2 A per diode	EAS	30	mJ
Operating junction temperature range	TJ	-55 to +150	°C
Storage temperature range	TSTG	-55 to +150	°C

Note:

- (1) Mounted on 30 mm x 30 mm Al P.C.B. with 50 mm x 25 mm x 100 mm fin heat sink
- (2) Free air, mounted on recommended copper pad area

Electrical characteristics (Tc=25°C unless otherwise noted)

Parameter	Symbol	Value		Unit
		Typical	Max	
Instantaneous forward voltage at IF=5A, Tj=25°C at IF=10A, Tj=25°C at IF=5A, Tj=125°C at IF=10A, Tj=125°C	VF	0.81 0.90 0.67 0.78	0.87 1.05 0.72 0.88	V
Maximum reverse current per leg Tj=25°C	IR	10		u'A
at working peak reverse voltage Tj=125°C		2		m'A

Thermal characteristics (Tc=25°C unless otherwise noted)

Parameter	Symbol	Value	Unit
Typical thermal resistance	RθJA	90	°C/W
	RθJM	4	


Notes:

- (1) Mounted on 30 mm x 30 mm Al P.C.B.; thermal resistance RθJM - junction to mount
- (2) Free air, mounted on recommended copper pad area

SD10PU200

High Current Density Surface Mount Schottky Rectifier

Characteristics Curve



SD10PU200

High Current Density Surface Mount Schottky Rectifier

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Bruckewell Technology Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Bruckewell"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product. Bruckewell makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Bruckewell disclaims

- (i) Any and all liability arising out of the application or use of any product.
- (ii) Any and all liability, including without limitation special, consequential or incidental damages.
- (iii) Any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Bruckewell's knowledge of typical requirements that are often placed on Bruckewell products in generic applications.

Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time.

Product specifications do not expand or otherwise modify Bruckewell's terms and conditions of purchase, including but not limited to the warranty expressed therein.