

# SS052D

## SWITCHMODE SCHOTTKY RECTIFIER

LCD Backlighting is Portable Devices  
 Digital Cameras and Camcorders  
 Mobile Phones and accessories  
 Notebooks, Electronic Books  
 GPS

### Features

- Ultra low VF - 420mV @ 500mA
- Ultra low VF - 360mV @ 300mA
- Low reverse current losses
- Negligible switching losses
- Extremely fast switching
- Meets MSL level 1, per J-STD-020

Solder dip 260 °C max. 10 s, per JESD 22-A111

- RoHS compliant package

### Mechanical Data

- Case : DFN 0805 case
- Packed with FRP substrate and epoxy under filled
- Molding compound meets UL 94 V-0 flammability
- Weight : 0.016 gram


### Packing & Order Information

3,000/Reel




**RoHS**  
COMPLIANT

### CASE: DFN-0805



### Graphic symbol



## SS052D

### SWITCHMODE SCHOTTKY RECTIFIER

#### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

##### Maximum Ratings (Tc=25°C unless otherwise noted)

Parameter	Symbol	SS052D	Unit
Maximum repetitive peak reverse voltage	VRRM	20	V
Working peak reverse voltage	VRWM	14	V
Maximum DC blocking voltage	VDC	30	V
Maximum average forward rectified current	IF(AV)	0.5	A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	IFSM	10	A
IAS = 2 A per diode			
Operating junction temperature range	TJ	-50 to +125	°C
Storage temperature range	TSTG	-50 to +150	°C

##### Notes:

Mounted on 2" Square PC Board with 1" Square Total Pad Size, PC Board FR4.

##### Electrical characteristics (Tc=25°C unless otherwise noted)

Parameter	Symbol	Value		Unit
		Typical	Max	
Instantaneous forward voltage at IF=0.3A, Tj=25°C at IF=0.5A, Tj=25°C	VF	0.34	0.50	V
		0.42		
Maximum reverse current per leg Tj=25°C	IR	20	100	u'A
at working peak reverse voltage Tj=125°C		5		m'A

##### Thermal characteristics (Tc=25°C unless otherwise noted)

Parameter	Symbol	Value	Unit
Typical thermal resistance	RθJL	15	°C/W
	Rthja	80	

##### Notes:

- (1) Pulse test: 300 μs pulse width, 1 % duty cycle
- (2) Pulse test: Pulse width ≤ 40 ms

## SS052D

### SWITCHMODE SCHOTTKY RECTIFIER

#### **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Bruckewell Technology Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Bruckewell"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product. Bruckewell makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Bruckewell disclaims

- (i) Any and all liability arising out of the application or use of any product.
- (ii) Any and all liability, including without limitation special, consequential or incidental damages.
- (iii) Any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Bruckewell's knowledge of typical requirements that are often placed on Bruckewell products in generic applications.

Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time.

Product specifications do not expand or otherwise modify Bruckewell's terms and conditions of purchase, including but not limited to the warranty expressed therein.